VIBE QUICK INSTALLATION GUIDE



REMOVING THE NECK CURTAIN

- Place your helmet upside down on a soft cloth on a flat surface.
- Start from the front of the helmet and gently pull on the neck curtain toward the center of the helmet



Slide the neck curtain out from the rear helmet portion.



REMOVING THE RIGHT CHEEK PAD

 Detach the Velcro and the three snaps by pulling the right cheek pad toward the inside of the helmet.



REMOVING THE REAR TRIM

Using either marking on the rear trim, push the trim away from the helmet by pressing directly on the trim.



REMOVING THE ACCESSORY COVERS

Remove the accessory cover by pulling it away from the helmet. Do this on both sides of the helmet.




REMOVING THE EPS

7. Remove the EPS piece (foam) located under the trim.



INSTALLING THE MAIN LINIT

- Place the main unit in the slot left by the EPS from the previous step.
- If you have the E LinQ option, remove the end cap on the RED connector.
- 3. Connect the left connector with the RED female connector on the helmet.



INSTALLING THE USER INTERFACE

4. Pass the wire sideways into the slot and hole on the left.



5. Slide the antenna into the hole and magnetically clip the user interface.



6. Make sure the user interface tab next to the wire is locked into the rectangular hole.



INSTALLING THE ANTENNA

7. Slide the antenna into the hole on the right.



8. Pass the wire into the slot and hole.

Place the cable so that it does not come into conflict with the magnet.



10. Reinstall the accessory cover.



OPTION A: SPEAKERS WITH NCS

1.1. Remove the NCS from the helmet (held by Velcro™).



1.2. Remove the foam cut-out from each NCS by ripping the center circle portion.



1.3. Remove the white foam inside the NCS.



1.4. Disconnect the speaker and pass the speaker connector.



1.5. Using the Velcro, position and attach the speaker inside the NCS.



1.6. Reinstall the NCS into the helmet.



1.7. Reconnect the speaker cable with the BLACK female connector from the main unit. Repeat on the other side.



OPTION B: SPEAKERS WITHOUT NCS

2.1. Remove the NCS from the helmet (held by Velcro).



- 2.2. Make sure the speaker wire is pointing toward the back of the helmet.
- 2.3. Adjust the speaker's position in the helmet to maximize comfort



MICROPHONE INSTALLATION

- Install the Velcro and apply uniform pressure on the adhesive.
- Install the microphone on the Velcro installed at the previous step on the inner right side of the helmet; guide the different wires to keep them out of reach.



3. Pass the wire in the intended groove and Velcro strap.



Make sure the RED connector is plugged in the right way with the arrow pointing toward the Sena logo.

REINSTALL REAR TRIM

- Place the connectors and cables in the cavity next to the main unit.
- Align one side of the rear trim, then push directly on the trim to reinstall it onto the helmet.

To minimize the risk of serious injury, death or product damage, read the complete user guide before using the product for the first time. Go to https://www.operatorsguides.brp.com/ to access the complete user guide.

AWARNING

Do not carry or hold the helmet by the chin curtain. The chin curtain may come off, causing the helmet to drop.

NOTICE

Do not pull directly on the electrical wires, as you could damage them.





Velcro™ is a registered trademark owned by Velcro IP Holdings LLC and its affiliates. Product may differ from picture shown.

®,™ and the BRP logo are trademarks of Bombardier Recreational Products Inc. or its affiliates. ©2023 Bombardier Recreational Products Inc. All rights reserved. Printed in China. HELMET-UMRO5EN



PAPER COLLECTION · COLLECTE DE PAPIER · PAPIERSAMMLUNG · COLECCIÓN DE PAPEL · RACCOLTA CARTA

Please check with local authorities waste collection rules. Vérifier les règles de collecte des déchets auprès de l'administration locale. Erkundigen Sie sich bei den örtlichen Behörden nach den Vorschriften für die Abfallsammlung. -Consulte a bas autoridades locales las reglas de recoglida de residuos. -Consultare le autorità locali per consocre le recole di raccolta dei rifinti.