



SUPPLEMENT

OPERATOR'S GUIDE LITOPIA® 205 SE

This Supplement must be used with 2005 Utopia® Operator's Guide (P/N 204 630 319).

🛝 WARNING

Read this guide thoroughly. It contains important safety information. Do not remove this Operator's Guide from the vehicle.

204 630 335

©™ TRADEMARKS OF BOMBARDIER RECREATIONAL PRODUCTS INC. OR ITS AFFILIATES. Bombardier is a trademark of Bombardier Inc. Used Under License. ©2004 Bombardier Recreational Products Inc. All Refits Reserved. Printed in Canada.

Dear Utopia® 205 SE Owner, This Supplement contains additional informations not included in the 2005 Operator's Guide 204 630 319) that may applies to your boat model.

TABLE OF CONTENTS

VEHICLE INFORMATION

CONTROLS, COMPONENTS AND INSTRUMENTS FUNCTIONS	4
Tower	4
Depth Finder	6
Stereo Remote Control	

VEHICLE INFORMATION

CONTROLS, COMPONENTS AND INSTRUMENTS FUNCTIONS

Tower

The Utopia[®] 205 SE has a model available with a tower for skiing/wake-boarding.



CAUTION: Always tow the vehicle with the towing tower fastened in the upright position to avoid damage to the boat and towing vehicle while in transport. Tower must be secured and in the upright position to avoid damage to the boat. Periodically check that bolts are in place and tight. Check clearance height around docks, shore, overhanging objects, bridges and power lines. The tower must not be used as a tie-down or tie-off point.

To clean the tower, use isopropyl alcohol and a clean soft cloth.

To fold tower for storage, remove knob below, from each side of tower.



1. Remove this knob

Carefully fold tower forward until storage pad is in contact with bow.

Remove knobs from curved extensions on each side of tower.



1. Remove this knob

Lower both support arms into position shown below.





Place knobs in glovebox or other secure storage for later use.

Raising of tower is the reverse of this procedure.

Tower Removal

NOTE: This procedure will require two people. Remove tower only from upright position.

To completely remove tower from boat, remove both rear attachment knobs from tower and remove the 8 mm (5/16 in) Allen bolt from each front tower upright. Carefully remove tower from boat.

Installation (from off boat)

NOTE: This procedure will require two people.

Carefully lift tower assembly and position front supports in their attachment points.

Apply Loctite 243 (P/N 293 800 059) to threads of bolts and install bolts into front attachment points. Torque bolts to 12 N•m (106 lbf•in).

Lift support arms into position and install knobs.

Raise tower into upright position and install knobs to complete installation of tower.

\land WARNING

Pulling a tube, skier or wakeboarder makes the boat handle differently and requires greater skill. Unless absolutely necessary, do not make tight, sharp turns. Keep a safe distance from docks, swimmers, other craft or objects. Be advised that serious injury can result if the tow rope becomes slack during a tight turn or when circling. The rope could become wrapped around the neck or limbs of a person.

The decal shown below is installed on the tower and on the gunwale next to the driver's seat.

A WARNING

Misuse of tower may cause severe injury or death.

- Use tower only for wakeboarding or water skiing.
- Do not allow tow rope to dangle or get entangled with occupants, boat or engine.
- Attach tow rope only at the center attachment point.
- Tow only 1 person at a time.
- Do not climb on, sit on or jump off tower.

F13L1PL

Depth Finder

A depth finder is included as standard equipment with the Utopia 205 SE and is located on the dashboard.



Please refer to included manufacturer's instruction sheet for depth finder operation.

Stereo Remote Control

A remote control for the AM/FM CD stereo is included as standard equipment with the Utopia 205 SE and is located on the dashboard.



Please refer to included manufacturer's instruction sheet for remote control operation.